

NOTES LEGEND:

- 1. NEW PRESSURE TREATED WOOD BLOCKING. AS REQUIRED TO MATCH DEPTH OF INSULATION.
- 2. NEW SPECIFIED INSULATION SYSTEM.
- 3. NEW PRE-MOLDED CANT SET IN ROOF CEMENT
- 4. ROOFING SYSTEM. SEE SECTION 07-55-00 APPENDIXC FOR ADDITIONAL INFORMATION
- 5. NEW .050 ALUMINUM EXPANSION JOINT COVER PER S.M.A.C.N.A.- FIGURE 5-5A.
- 6. NEW 2 X12 PRESSURE TREATED WOOD. BLOCKING.
- 7. FASTENERS WITH NEOPRENE WASHERS THROUGH SLOTTED HOLES 12" O.C.
- 8. NEW SPECIFIED EXPANSION JOINT COVER-SHOP FABRICATE ALL TRANSITIONS, CORNERS, AND BENDS 24" FROM EDGES. ENGAGE TO CLEAT AND SECURE AT 12"O.C. WITH SPECIFIED FASTENERS IN SLOTTED HOLES. CONNECT PIECES WITH 1-INCH STANDING SEAMS
- 9. EXPANSION JOINT WIDTH TO AS DETERMINED BY STRUCTURAL ENGINEER.

TITLE: STANDARD EXPANSION JOINT

SPEC.SECTION: 07-60-00.01 APPENDIX A

DATE: 07/11/2019

